

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 April 2005 (28.04.2005)


PCT

(10) International Publication Number
WO 2005/038190 A1

- (51) International Patent Classification⁷: **E21B 17/02**,
H01R 13/52, 13/523
- (21) International Application Number:
PCT/EP2004/052471
- (22) International Filing Date: 7 October 2004 (07.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
03256384.3 9 October 2003 (09.10.2003) EP
- (71) Applicant (for all designated States except CA, US): **SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).
- (71) Applicant (for CA only): **SHELL CANADA LIMITED** [CA/CA]; 400 - 4TH Avenue S.W., Calgary, Alberta T2P 2H5 (CA).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **GRIFFITHS, Neil** [GB/NL]; Kesslerpark 1, NL-2288 GS Rijswijk (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: METHOD FOR INTERCONNECTING ELECTRICAL CONDUITS IN A BOREHOLE



(57) Abstract: A method for interconnecting electrical conduits in an underground borehole by means of a self-cleaning downhole electrical connector with a static and a moveable connector part (4,3), comprises installing the static connector part (4) within the borehole such that a central throughbore (7) within the static part (4) provides a passage for fluid and debris passage and for access there beneath after retrieval of the moveable connector part (3); and lowering the moveable connector part (3) on top of the static connector part (4) such that pairs of electrical contacts (8 and 11A-C) of the static and movable connector parts (4,3) intermesh and fluid and debris is discharged via the central throughbore into the section of the borehole beneath the static connector part. The connector may be used to connect a wireline retrievable electrical submersible pump (ESP) system (2) to an electrical power supply line (5) which may remain in the borehole when the ESP system (2) is retrieved for inspection, repair or replacement.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.